

## Rockbrake<sup>®</sup> Product Range

Grade	Length	Max. shot > 125 micron	Surface treatment	Typical property	Packaging
Rockbrake <sup>®</sup> RB210–Roxul <sup>®</sup> 1000	150 ± 25 µm	0.20%	silane/ rubber	very low shot, improved bonding, easy processing, improved NVH in NAO non steel disc pads	20 kg/bag 500 kg/pallet
Rockbrake <sup>®</sup> RB215ELS–Roxul <sup>®</sup> 1000	150 ± 25 µm	0.10%	silane	extreme low shot, low friction material and rotor wear, improved bonding	20 kg/bag 500 kg/pallet
Rockbrake <sup>®</sup> RB220ELS–Roxul <sup>®</sup> 1000	230 ± 50 µm	0.10%	silane	extreme low shot, low friction material and rotor wear, improved bonding	16 kg/bag 400 kg/pallet
Rockbrake <sup>®</sup> RB215–Roxul <sup>®</sup> 1000	150 ± 25 µm	0.20%	silane	very low shot, easy dispersion, low wear, improved bonding	20 kg/bag 500 kg/pallet
Rockbrake <sup>®</sup> RB220–Roxul <sup>®</sup> 1000	230 ± 50 µm	0.20%	silane	very low shot, low wear, improved bonding	16 kg/bag 400 kg/pallet
Rockbrake <sup>®</sup> RB250–Roxul <sup>®</sup> 1000	125 ± 25 µm	1.0%	none	low shot, short fibre with easy dispersion	25 kg/bag 500 kg/pallet*
Rockbrake <sup>®</sup> RB260–Roxul <sup>®</sup> 1000	300 ± 50 µm	0.20%	none	very low shot, low wear, long fibre	16 kg/bag 400 kg/pallet
Rockbrake <sup>®</sup> RB280–Roxul <sup>®</sup> 1000	650 ± 150 µm	0.20%	cationic	very low shot, long fibre mainly meant for wet mixes	7 kg/bag 210 kg/pallet
Rockbrake <sup>®</sup> RB295–Roxul <sup>®</sup> 1000	125 ± 25 µm	5.0%	none	lower shot, easy dispersion	25 kg/bag 500 kg/pallet*
Rockbrake <sup>®</sup> RB297–Roxul <sup>®</sup> 1000	300 ± 50 µm	20%	none	medium shot, relative long fibre	15 kg/bag 450 kg/pallet
Rockbrake <sup>®</sup> RBC300–Roxul <sup>®</sup> 1000	max 200 µm	30%	none	medium to high shot	25 Kg/bag 500 Kg/ pallet*

\* To increase the amount in a container, these products can be packed in 25 kg bags on 625 Kg pallets